



軸径 d _f (mm)	呼び番号	寸														重量 (kg)
		k	a	b	c	l	w	m	u	v	D	g	t	s	呼び	
25	SN506	50	185	52	22	77	90	150	15	20	62	30	M8	M12	1.6	
30	SN507	50	185	52	22	82	95	150	15	20	72	33	M10	M12	1.9	
35	SN508	60	205	60	25	85	110	170	15	20	80	33	M10	M12	2.6	
40	SN509	60	205	60	25	85	112	170	15	20	85	31	M10	M12	2.8	
45	SN510	60	205	60	25	90	115	170	15	20	90	33	M10	M12	3.0	
50	SN511	70	255	70	28	95	130	210	18	23	100	33	M12	M16	4.0	
55	SN512	70	255	70	30	105	135	210	18	23	110	38	M12	M16	4.6	
60	SN513	80	275	80	30	110	150	230	18	23	120	43	M12	M16	5.4	
65	SN515	80	280	80	30	115	155	230	18	23	130	41	M12	M16	6.7	
70	SN516	95	315	90	32	120	175	260	22	27	140	43	M16	M20	8.5	
75	SN517	95	320	90	32	125	185	260	22	27	150	46	M16	M20	9.3	
80	SN518	100	345	100	35	145	195	290	22	27	160	62.4	M16	M20	12	
85	SN519	112	345	100	35	140	210	290	22	27	170	53	M16	M20	14	
90	SN520	112	380	110	40	160	218	320	26	32	180	70.3	M20	M24	16	
100	SN522	125	410	120	45	175	240	350	26	32	200	80	M20	M24	20	
110	SN524	140	410	120	45	185	270	350	26	32	215	86	M20	M24	24	
115	SN526	150	445	130	50	190	290	380	28	36	230	90	M24	M24	30	
125	SN528	150	500	150	50	205	305	420	33	42	250	98	M24	M30	38	
135	SN530	160	530	160	60	220	325	450	33	42	270	106	M24	M30	45	
140	SN532	170	550	160	60	235	345	470	33	42	290	114	M24	M30	50	

自動誘心軸受 呼び番号	位置決めの輪		自動誘心ころ軸受 呼び番号		位置決めの輪		オイルシール		呼び番号
	呼び番号	個数	呼び番号	個数	呼び番号	個数	呼び番号	個数	
	1206K+H206X	SR 62X 7	2	—	—	—	—	—	
2206K+H306X	SR 62X 10	2	—	—	—	—	—	—	SN506
1207K+H207X	SR 72X 8	2	—	—	—	—	—	—	SN507
2207K+H307X	SR 72X 10	2	—	—	—	—	—	—	SN507
1208K+H208X	SR 80X 7.5	2	—	—	—	—	—	—	SN508
2208K+H308X	SR 80X 10	2	22208CK+H 308X	SR 80X 10	1	ZF 8	2	—	SN508
1209K+H209X	SR 85X 6	2	—	—	—	—	—	—	SN509
2209K+H309X	SR 85X 8	2	22209CK+H 309X	SR 85X 8	1	ZF 9	2	—	SN509
1210K+H210X	SR 90X 6.5	2	—	—	—	—	—	—	SN510
2210K+H310X	SR 90X 10	2	22210CK+H 310X	SR 90X 10	1	ZF 10	2	—	SN510
1211K+H211X	SR 100X 6	2	—	—	—	—	—	—	SN511
2211K+H311X	SR 100X 8	2	22211BK+H 311X	SR 100X 8	1	ZF 11	2	—	SN511
1212K+H212X	SR 110X 8	2	—	—	—	—	—	—	SN512
2212K+H312X	SR 110X 10	2	22212BK+H 312X	SR 110X 10	1	ZF 12	2	—	SN512
1213K+H213X	SR 120X 10	2	—	—	—	—	—	—	SN513
2213K+H313X	SR 120X 12	2	22213BK+H 313X	SR 120X 12	1	ZF 13	2	—	SN513
1215K+H215X	SR 130X 8	2	—	—	—	—	—	—	SN515
2215K+H315X	SR 130X 10	2	22215BK+H 315X	SR 130X 10	1	ZF 15	2	—	SN515
1216K+H216X	SR 140X 8.5	2	—	—	—	—	—	—	SN516
2216K+H316X	SR 140X 10	2	22216BK+H 316X	SR 140X 10	1	ZF 16	2	—	SN516
1217K+H217X	SR 150X 9	2	—	—	—	—	—	—	SN517
2217K+H317X	SR 150X 10	2	22217BK+H 317X	SR 150X 10	1	ZF 17	2	—	SN517
1218K+H218X	SR 160X 16.2	2	—	—	—	—	—	—	SN518
2218K+H318X	SR 160X 11.2	2	23218BK+H2318X	SR 160X 11.2	2	ZF 18	2	—	SN518
1219K+H219X	SR 170X 0.5	2	—	—	—	—	—	—	SN519
2219K+H319X	SR 170X 10	2	22219BK+H 319X	SR 170X 10	1	ZF 19	2	—	SN519
1220K+H220X	SR 180X 18.1	2	—	—	—	—	—	—	SN520
2220K+H320X	SR 180X 12.1	2	22220BK+H 320X	SR 180X 12.1	2	ZF 20	2	—	SN520
1222K+H222X	SR200X 21	2	—	—	—	—	—	—	SN522
2222K+H322X	SR200X 13.5	2	23222BK+H2322X	SR200X 13.5	1	ZF 22	2	—	SN522
—	—	—	22224BK+H3124X	SR215X 14	2	ZF 24	2	—	SN524
—	—	—	23224BK+H2324X	SR215X 10	1	—	—	—	SN524
—	—	—	22226BK+H3126	SR230X 13	2	ZF 26	2	—	SN526
—	—	—	23226BK+H2326	SR230X 10	1	—	—	—	SN526
—	—	—	22228BK+H3128	SR250X 15	2	ZF 28	2	—	SN528
—	—	—	23228BK+H2328	SR250X 10	1	—	—	—	SN528
—	—	—	23230BK+H3130	SR270X 16.5	2	ZF 30	2	—	SN530
—	—	—	23230BK+H2330	SR270X 10	1	—	—	—	SN530
—	—	—	22232BK+H3132	SR290X 17	2	ZF 32	2	—	SN532
—	—	—	23232BK+H2332	SR290X 10	1	—	—	—	SN532

- 備考 (1) SN524以上には吊り上げ用アイボルトが付きます。
 (2) クーレスニップルは御要求により付けます。サイズはSN520以下PT $\frac{1}{2}$ 、SN522以上PT $\frac{3}{4}$ (SN506・SN507は6mm)
 (3) 位置決め輪は御要求により付けます。
 (4) 片面で使用される場合は御要求により盲ボタを付けます。
 (片首形記号: FM+軸受の内径番号)